

HQL40A DTH HAMMER

HQL4A. Hammers	Item Description	Weight (Kg)	Part Number	
	1	Top Sub	6.50	HQL40A-TSUB
	2	"O"Ring of Top Sub	0.01	HQL40A-SR-TSUB
	3	Check Valve	0.35	HQL40A-CVALVE
	4	Spring	0.05	HQL40A-SPRING
	5	Air Distributor	1.50	HQL40A-CBUFFER
	6	Internal Cylinder	2.10	HQL40A-DIST
	7	Piston	8.50	HQL40A-ICYL
	8	External Cylinder	15.20	HQL40A-PISTON
	9	Guided Sleeve	1.80	HQL40A-ECYL
	10	"O" Ring of Stop Ring	0.005	HQL40A-SR-SRING
	11	Stop Ring	0.20	HQL40A-SRING
	12	Drive Chuck	3.20	HQL40A-DCHUCK
	13	Drill Bit		HQL40A-115FF-TV

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
1070mm	40.0Kg	Φ99	QL40 HQL40	Φ112-Φ127	API 2 3/8 " REG
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	Air Consumption		
			200-300(Psi)		
1230x155x180mm	30HZ	25-40r/min	500-700(CFM)		